

High-Power-LED-Schienenstrahler

High power LED track lights

BAUART:
DESIGN:

High-Power-LED-COB-Schienenstrahler in hochwertigen Aluminium-Druckgussgehäusen, 360° dreh- und schwenkbar (30 W nur 90° schwenkbar), mit Frontscheibe. Mit Adapter für 3-Phasen-Euro-Schienensystem. Mit Befestigungsöse für Sicherungsseil (nicht 30 W). Lichtfarbe per Schalter umstellbar (nur 45 W und 90 W): 3000 K, 4000 K, 5700 K. Abstrahlwinkel kann durch Austausch der Streulinse (Sonderzubehör) geändert werden. Flickerfreie LED. CRI > 90. Komplettsystem mit integriertem Netzteil. Passiv gekühlt (ohne Ventilator).

High power LED COB track lights in high quality die-cast aluminium housing, 360° turnable/tiltable (30 W 90° tiltable only), with front glass. With adapter for 3-phase-Euro-track-system. With lug for safety wire (45 W and 90 W only). Beam angle adjustable by exchanging the front lens (optional). Flicker free LED. CRI > 90. Integrated power supply. Passive cooling (without fan).

INFO:

Die Helligkeit des 2 x 45 W Schienenstrahlers entspricht ungefähr der Helligkeit eines 150 W-HQI-Schienenstrahlers.

The 2 x 45 W track light is almost as bright as a 150 W-HQI- track light.



Praktisch so hell wie 150 W HQI bzw. 70 W HQI

Lichtfarbe einstellbar (nur 45 und 90 W):
3000 K, 4000 K, 5700 K

Typ/Model	Leistung/ Power	Helligkeit/ Brightness	Abstrahlwinkel/ Beam angle	Lichtfarbe/ Color temp.	Maße/Dimensions	Gewicht/Weight
149 341 030	30 W	3200 lm	60°, 24°*	NW, CW*, WW*	135 x 85 x 180 mm	0,8 kg
149 345 045	45 W	3800-4500 lm	60°, 20°*	NW-CW-WW einstellbar	275 x 150 x 95 mm	1,3 kg
149 346 090	2 x 45 W	7600-9000 lm	60°, 20°*	NW-CW-WW einstellbar	275 x 248 x 95 mm	2,2 kg

WW = ~3000 K warmweiß / warmwhite, NW = ~4000 K neutralweiß / neutralwhite, CW = ~6000 K kaltweiß / coolwhite
* optional / optional